

# Accessories...

Spray Guns • Clips • Clamps • Valves • Hose Tails • Seals • Compressions



# Accessories...

Spray Guns • Clips • Clamps • Valves • Hose Tails • Seals • Compressions

**FlexTECH** provide a comprehensive selection of hose accessories from clips and clamps, hose tail fittings etc to push-in connectors and wash-down spray guns.

These accessories are available in a diverse range of materials and often overlooked as an essential for the majority of low pressure hose and tube applications.

Flextech also have immediate access to over 500 additional products and accessories which complement our range of hose, assemblies and couplings.

The additional products are detailed in our new 1,500 page catalogue and generally available for immediate delivery.



### Spray Guns & Nozzles

**FlexTECH** offer a full range of wash down, pneumatic and diesel / fuel guns. Manufactured from brass, stainless or plated steel these guns are designed specifically to compliment the extensive range of hose and tubes available in today's market.

A full range of heavy duty high pressure to medium or low pressure guns for all applications is available.



### Brass Hose Tail Fittings

Standard and commonly used barbed hose tail connector with either male or female BSP / NPT thread.

From 1/8" to 2" with a multitude of step up size configurations.

Now available with chrome plated finish.



### Geka Irrigation Couplings

These quick disconnect brass water fittings are used for many different applications in the agriculture and horticulture industries.

Widely used in the irrigation of parks, golf courses, garden centres, cricket and football pitches these fittings are well suited for use with high quality yellow irrigation hoses.



### Valves

A full range of manually operated brass stainless steel or polypropylene Ball and Gate valves are available in sizes from 1/8" to 3" in.

Manufactured to ISO standards with pressure ratings from 10 Bar to 40 Bar.



### Stainless Fittings

A comprehensive range of 316 stainless steel 150psi rated fittings manufactured to ISO 7.1, BS21, DIN 2999 and ISO 228.

Suitable for temperatures up to +400°C these fittings come as standard with BSP threads, elbows, tee's, straight's, hose tails and crosses.



### Brass Lugged Hose Tails

Lugged hose tails are available in Stainless Steel, Brass, Aluminium, Malleable Iron and Gun Metal with either BSP / URT male and female threads.

Options for flanged hoses available to order. These fittings range in size from 1/2" to 6" and are ideal for low pressure.



### Polypropylene Fittings

**FlexTECH** range of polyprop moulded hose tail fittings are manufactured to ISO228 and available with either male or female threaded hose tails in sizes from 1.1/2" to 4" with URT threads in 3" and 4".

These are tough lightweight 10 Bar rated fittings suitable for many applications.



### Flanged Hose Tails

**FlexTECH** range of flange hose tails and combination nipples are free from lugs and designed to eliminate the need to have hoses made with enlarged ends since the hose stem is swaged to suit the hose ID.

They are available in steel and stainless steel in sizes from 1/2" to 4".



### Strainers

A range of hose tail and tin can strainers manufactured from carbon or stainless steel for use with water and other fluids.

Sizes available from 1/2" to 8" with optional BSP male thread.



### Plastic fittings

Manufactured from Polypropylene or Nylon these high performance connectors have good chemical resistance, are suitable for up to 200psi and rated for temperatures to +70°C.

Available in an assortment of connections including Tee, Straight, Reducer, Elbows.



### Heavy Duty Bolt Clamps

These clamps constructed from stainless steel or low carbon mild steel with zinc plating are manufactured in an extensive range of sizes from 17 to 260mm.

Their wide band width and single bolt enables maximum torque which is far greater than conventional hose clips.




### Wormdrive Hose Clips

Wormdrive clips are ideal for temporary or semi permanent connections on all types of hose with low working pressures.

These clips are available in zinc plated mild steel or 304 / 316 stainless steel.

Size range is from 10 - 600mm diameter.



### 'O' Clips

'O' clips are suitable for low pressure applications requiring a permanent fixture with simplicity. They can be removed by snipping one of the ears with pincers.


Available in zinc plated mild steel or 304/316 stainless steel and come with either a single or double ear clip method.



### Pneumatic Fittings

A comprehensive assortment of 'Push Fit' compression fittings ideally suited for use with pneumatic nylon or polyurethane tube.

These versatile fittings are suitable for up to 15 Bar pressure and available in either metric or imperial options.



### Hamlet Compression Fittings

Fully interchangeable with Swagelok these twin ferrule compression fittings are the perfect cost effective alternative.

Available in metric and imperial sizes from 3 to 25mm (and 1/8" to 1") with BSP or NPT threads and manufactured in brass or 316 stainless steel options.